

MF Bag Natural

Spec 160

End use

Longview's bag and wrapping paper grades are made from highly refined pulp in a variety of basis weights and percentages of recycled fiber content. Our bag and wrapping paper grades are valued for their cleanliness, strength, sustainability and end-use possibilities.

Longview offers a variety of grades featuring different sheet characteristics and recycled fiber content for use in multiple bag and wrapping applications. Our industrial wrapping papers are converted and used for building and construction, automotive parts, interleaving, retail wrapping, void fill or cushioning wrap (used in packing to prevent breakage), and more.

Sustainable solutions. Multiple applications.

Options

Our machine finish kraft paper is available in a variety of basis weights ranging from 28 to 67 lbs/3000 ft².

Compliance

Longview's MF paper is manufactured in compliance with FDA, CONEG and RoHS regulations. Our paper is routinely tested to ensure that strict substance limits are met.

Sustainable

At Longview, our products start from trees, a renewable resource. Our paper is made from virgin wood pulp fiber, recycled fiber, or a combination of the two. Our virgin furnish, a blend of Northern softwoods including Douglas fir, pine, hemlock and spruce, provides superior strength properties in our paper.

<u>Property</u>	<u>Units</u>	<u>Typical Values</u>							<u>Test Method</u>
Substance	lbs. / 3000 ft ²	28	30	33	35	38	40		ISO 536
Caliper	Mils	2.8	3.0	3.3	3.5	3.8	3.9		TAPPI T411
Tensile MD	Lbs/inch	21.9	23.5	26.2	27.5	29.8	29.5		ISO 1924-3
Tensile CD	Lbs/inch	9.3	9.1	10.2	11.4	13.6	12.5		ISO 1924-3
Tear MD	Grams	48	50	56	63	74	76		ISO 1974
Tear CD	Grams	57	62	69	77	89	92		ISO 1974
Porosity	Sheffield	228	225	230	232	245	240		ISO 5636-3
Burst	psi	23	24	27	29	34	32		TAPPI T403
Moisture	%	7.0	7.0	7.0	7.0	7.2	7.1		

Laboratory conditions 73.4 °F, 50% RH (ISO 554-1976)

Product Info: info@longfibre.com
 Phone toll free: 877.734.9321
 Outside the U.S.: +1.360.442.7739
 Fax: +1.360.575.6116
longviewfibre.com

