

TEA-KRAFT® Porous

Spec 2406

End Use

TEA-Kraft® is a semi-extensible, high-performance multiwall sack paper for three-ply applications. It is ideal for use in three-ply bags such as pasted valve bags with microperforations where low Gurley porosity is not critical.

TEA-Kraft is designed for industrial sacks with various types of sack construction: pasted valve and pinched-bottom open mouth.

TEA-Kraft end-use sack applications include: cement building materials, chemicals, baking products, pet foods and more.

Compliance

TEA-Kraft is manufactured in compliance with FDA, CONEG and RoHS regulations. Our paper is thoroughly tested to ensure that strict substance limits are met.

Sustainable

At Longview, our products start from trees, a renewable resource. Our TEA-Kraft paper is made from virgin wood pulp fiber. Our virgin furnish, a blend of Northern softwoods including Douglas fir, pine, hemlock and spruce, provides superior strength properties in our paper.

<u>Property</u>	<u>Units</u>	<u>Typical Values</u>						<u>Test Method</u>
Substance	gsm	70	80	85	90	95	98	ISO 536
Tensile MD	kN/m	4.9	5.6	6.0	6.3	6.7	6.8	ISO 1924-3
Tensile CD	kN/m	3.9	4.5	4.7	5.0	5.3	5.4	ISO 1924-3
Stretch MD	%	6.5	6.5	6.5	6.5	6.5	6.5	ISO 1924-3
Stretch CD	%	7.5	7.5	7.5	7.5	7.5	7.5	ISO 1924-3
TEA MD	J/m ²	185	212	225	238	251	258	ISO 1924-3
TEA CD	J/m ²	185	212	225	238	251	258	ISO 1924-3
Tear MD	mN	1334	1530	1619	1638	1736	1776	ISO 1974
Tear CD	mN	1491	1697	1805	1903	2001	2060	ISO 1974
Cobb 1 Min.	g/m ²	30	30	30	30	30	30	ISO 535
Porosity	Sec/100 cc	5	5	5	5	5	5	ISO 5636-3
Moisture	%	7.5	7.5	7.5	7.5	7.5	7.5	

Laboratory conditions 73.4 °F, 50% RH (ISO 554-1976)



See how we stack up.

Visit us online. Discover what we can do for you.
Call or email a representative today.

Product Info: info@longfibre.com
Phone toll free: 877.734.9321
Outside the U.S.: +1.360.442.7739
Fax: +1.360.575.6116
longviewfibre.com



TRUE CRAFT®