

TEA-KRAFT[®] Rigid MWS

Spec 2492

End Use

TEA-Kraft[®] Rigid Wet Strength is a semi - extensible, high-performance multiwall sack paper for three-ply applications.

TEA-Kraft Rigid MWS is designed for superior machine direction stiffness for improved converting and filling with good strength properties.

TEA-Kraft Rigid MWS end-use sack applications include: sewn open mouth and pinch bottom bags for food, pet food, potato baler and non-dusty chemicals sacks where additional wet tensile strength is required.

Compliance

TEA-Kraft is manufactured in compliance with FDA, CONEG and RoHS regulations. Our paper is thoroughly tested to ensure that strict substance limits are met.

Sustainable

At Longview, our products start from trees, a renewable resource. Our paper is made from virgin wood pulp fiber, recycled fiber, or a combination of the two. Our virgin furnish, a blend of Northern softwoods including Douglas fir, pine, hemlock and spruce, provides superior strength properties in our paper.

<u>Property</u>	<u>Units</u>	<u>Expected Values</u>		<u>Test Method</u>
Substance	gsm	80	98	ISO 536
Tensile MD	kN/m	7.7	9.4	ISO 1924-3
Tensile CD	kN/m	4.4	5.3	ISO 1924-3
Wet Tensile MD	kN/m	1.5	1.9	ISO 1924-3
Stretch MD	%	3.0	3.0	ISO 1924-3
Stretch CD	%	7.5	7.5	ISO 1924-3
TEA MD	J/m ²	131	161	ISO 1924-3
TEA CD	J/m ²	219	267	ISO 1924-3
Tear MD	mN	1197	1422	ISO 1974
Tear CD	mN	1334	1697	ISO 1974
Porosity	sec/100 cc	15	15	ISO 5636-3
Cobb 1 Min.	g/m ²	30	30	ISO 535
Moisture	%	7.5	7.5	

Laboratory conditions 73.4 °F, 50% RH (ISO 554-1976)

See how we stack up.

Visit us online. Discover what we can do for you.
Call or email a representative today.

Product Info: info@longfibre.com
Phone toll free: 877.734.9321
Outside the U.S.: +1.360.442.7739
Fax: +1.360.575.6116
longviewfibre.com



TRUE CRAFT[®]